



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



RECESSED ACCESS DOOR AT-5020

Application

- For flush installation in walls or ceilings when it is required to conceal the door panel

Product Features

- Door is recessed 1"

AT-5020 Access Door Specifications:

Material: Steel : 16 gage door, 14 gage mounting frame

Door: Recessed 1"

Door Frame: 14 gage mounting frame

Hinge: Concealed, pivoting rod type, for wall applications over 24"x24" we suggest a concealed pins hinge

Standard Latch: Flush to surface, screwdriver operated cam latch

Optional Latches/Locks: Cylinder lock and key, allen head cam latch, spanner head cam latch

Finish: Steel: 5-stage iron phosphate preparation with prime coat of White alkyd baking enamel



AVAILABLE SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		WEIGHT PER DOOR		
inches	mm	Latches	lbs.	kg.
12 X 12	305 X 305	1	7	3.2
18 X 18	457 X 457	2	13	5.9
24 X 24	610 X 610	2	21	9.5
24 X 36	610 X 914	4	30	13.8

Wall or ceiling opening is W + 3/8" (9 mm)
For detailed specifications see submittal sheet

