



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



UNIVERSAL FLUSH ED-2002

Application

- Installation in Drywall, Plaster, Masonry, Tile or any flush surface
- Economical and attractive access door for walls & ceilings

Product Features

- Formed door panel
- Concealed hinge

ED-2002 Access Door Specifications:

Material: 18 gauge steel door and frame

Door: Flush to frame with reinforced edges

Door Frame: 1" wide outside flange with 1 1/2" deep (2.5 x 3.8cm) mounting frame
Knock over mounting tabs provided on 6x6, 8x8, 10x10 and 12x12

Hinge: Concealed Hinge Pin

Latch: Stainless steel screwdriver operated cam latch

Optional Latches/Locks: Cylinder lock and key, allen head cam latch, spanner head cam latch

Finish: 5 Stage iron phosphate preparation with prime coat of White alkyd baking enamel



AVAILABLE SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		Latches	WEIGHT PER DOOR	
inches	mm		lbs.	kg.
6 X 6	152 X 152	1	1.7	0.8
8 X 8	203 X 203	1	2.5	1.1
10 X 10	254 X 254	1	3.5	1.6
12 X 12	305 X 305	1	4.6	2.1
14 X 14	355 X 355	1	5.8	2.6
16 X 16	406 X 406	2	7.2	3.3
18 X 18	457 X 457	2	8.8	4.0
20 X 20	500 X 500	2	10.4	4.7
24 X 24	610 X 610	4	14.2	6.4

Wall or ceiling opening is nominal door size + 3/8" (9 mm)
For detailed specifications see submittal sheet

