



High-quality, architecturally pleasing, innovative access doors for walls, ceilings, ducts, floors and roofs



FIRE RATED INSULATED - UPSWING DOOR FOR CEILINGS FW-5050-UP

Application

- An insulated, fire rated access door for inward opening in ceilings

Product Features

- For fire rated ceilings, this door has been approved by Warnock Hersey International for 3 hours (max. size to 24" x 36")
- Insulated Door Panel
- Self-Closing
- Self-Latching
- Inside Latch Release

FW-5050-UP Access Door Specifications:

Material: Steel or Stainless Steel

Door: 16 gauge, Flush to frame with reinforced edges filled with 2" thick fire insulation

Mounting Frame: 16 gauge mounting frame, with trim 1" wide

Hinge: Concealed with coil spring for dampening

Fire Rating: Warnock Hersey International - 3 hours rated in a non-combustible ceiling, 1 hour rated in a combustibile ceiling. Max size 24"x36"

Standard Latch: L Handle - operable from both sides

Finish: Steel: 5 stage iron phosphate preparation with prime coat of white baked enamel.

Stainless Steel: Type 304 - #4 satin polish



AVAILABLE SIZES (Special sizes available upon request)

NOMINAL DOOR SIZE W X H		Latches	WEIGHT PER DOOR	
inches	mm		lbs.	kg.
22 X 36	560 X 914	2	35	15.9
24 X 24	610 X 610	1	28	12.7
24 X 36	610 X 914	2	38	18.1

Wall or ceiling opening is W + 3/8" (9 mm)
For detailed specifications see submittal sheet

