

ACD-2064

SPECIALTY DOORS

Recessed Acoustical Access Door for Drywall

Highest STC & OITC Rating in the INDUSTRY

Application

This recessed access door is ideal for use on Acoustical drywall walls where maintaining STC (Sound Transmission Class) and OITC (Outdoor-Indoor Transmission Class) is required. The unique taping bead flange allows for a concealed finish.

Product Features

- Zinc coated steel provides superior corrosion resistance
- Drywall taping bead flange
- Recessed door fitted with 5/8" thick drywall, ensures finish similar to surrounding
- Tested and evaluated to ASTM: E90(09), ASTM: E413(16), ASTM: E1332(16) and certified to STC Rating 64 and OITC Rating 53

ACD-2064 Specifications:

Material: 18 Gauge Satin Coat Steel

Door: 18 Gauge recessed design filled with 1½" thick acoustic mineral liner, 0.11" thick mineral filled vinyl barrier and fitted with 5/8" thick drywall as finished face

Frame: 18 Gauge, press bent for strength and rigidity, drywall taping bead flange
Insulated with 1" thick acoustical mineral liner

Gasket: Silicone perimeter seal gasket

Hinge: Continuous exposed stainless steel piano hinge

Standard Lock: Screw driver operated Compression Latch

Optional Lock: Compression Latch with Hex Head, Hex with security pin, Square, Triangle

Acoustic Rating: This door has been tested and evaluated to ASTM: E90(09), ASTM: E413(16), ASTM: E1332(16) and certified to STC Rating 64 and OITC Rating 53.

Finish: Satin Coat Steel



ACD-2064 STANDARD SIZES

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
12 x 12	305 x 305	1	13.2	6
18 x 18	457 x 457	1	24.3	11
24 x 24	610 x 610	1	41.9	19
24 x 36	610 x 914	2	62.0	28

