

# ACF-2064

## SPECIALTY DOORS Steel Flush Acoustical Access Door

Highest STC & OITC Rating in the INDUSTRY

### Application

- This flush access door is ideal for use on Acoustical walls where maintaining STC Rating (Sound Transmission Class) and OITC Rating (Outdoor-Indoor Transmission Class) is required

### Product Features

- Zinc coated steel provides superior corrosion resistance
- Type 304 Stainless steel with #4 satin polish also available
- Tested and evaluated to ASTM: E90(09), ASTM: E413(16), ASTM: E1332(16) and certified to STC Rating 64 and OITC Rating 54

### ACF-2064 Door Specifications:

**Material:** 18 Gauge Satin Coat Steel

**Door:** 18 Gauge, encapsulated design with 2" thick acoustical mineral liner and 0.11" thick mineral filled vinyl barrier

**Frame:** 18 Gauge, press bent for strength and rigidity, with 1" wide trim flanges and 1" thick acoustical mineral liner

**Gasket:** Silicone perimeter seal gasket

**Hinge:** Continuous exposed stainless steel piano hinge

**Standard Lock:** Screw driver operated Compression Latch

**Acoustic Rating:** This door has been tested and evaluated to ASTM: E90(09), ASTM: E413(16), ASTM: E1332(16) and certified to STC Rating 64 and OITC Rating 54.

**Finish:** 5 stage iron phosphate preparation with prime coat of white baked-on enamel



### ACF-2064 STANDARD SIZES

Nominal Door Size W&H		Weight per Door		
Inches	mm	Latches	lbs.	kg.
12 x 12	305 x 305	1	14.3	6.5
18 x 18	457 x 457	1	26.5	12
24 x 24	610 x 610	1	44.0	20
24 x 36	610 x 914	2	64.0	29

