

DW-5040

Flush Access Door, for Drywall

Application

- Designed specifically for installation in drywall walls and ceilings **after** the drywall has been installed

Product Features

- Formed door panel with flanges on four sides
- Unique concealed hinge, door flange is a perforated tapping bead with pre-punched holes

DW-5040 Access Door Specifications:

Material: 20 gauge galvanized formed door panel, 26 gauge galvanized frame

Door: Formed door panel with multiple bends for added strength, flanged on four sides, Integral perforated tapping bead adds rigidity

Hinge: Concealed

Standard Latch: Slotted Screwdriver Cam Latch

Optional Latches/Locks: Cylinder lock & key; allen head cam latch; spanner head cam latch, torx, torx head with security pin

Finish: 5 stage iron phosphate preparation with white baked-on polyester powder coat on door panel. Frame to be mill finish



DW-5040 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Latches	Weight per Door	
Inches	mm		lbs.	kg.
6 X 6	152 X 152	1	1.4	0.64
8 X 8	203 X 203	1	1.8	0.82
10 X 10	254 X 254	1	2.6	1.18
12 X 12	305 X 305	1	3.5	1.59
12 X 24	305 X 610	1	4.5	2.04
14 X 14	355 X 355	1	4.4	2.00
16 X 16	406 X 406	1	4.8	2.18
16 X 24	457 X 610	1	5.0	2.27
18 X 18	457 X 457	1	6.5	2.95
18 X 24	457 X 610	1	8.25	3.74
22 X 22	560 X 560	1	10.2	4.62
24 X 24	610 X 610	1	12.3	5.58
24 X 36	610 X 914	2	17.8	8.07
24 X 48	610 X 1219	2	15.0	6.80
30 X 30	762 X 762	2	17.3	7.85
36 X 36	914 X 914	2	23.0	10.43
36 X 48	914 X 1219	2	25.0	11.34

Wall or ceiling opening is W + 3/8" (9 mm)

For detailed specifications see submittal sheet

