



DIRECTION OF EXIT →

- NOTES:
- 1- MATERIAL: ALUMINUM
 - 2- LOADING: 300 LBS. PER SQ. FT.
 - 3- STAINLESS STEEL 316 HARDWARE
 - 4- COVERS NOT SUBJECTED TO VEHICULAR TRAFFIC LOADING (SIDEWALKS AND PARKWAYS, EXCLUDING DRIVEWAYS)
 - 5- ENCLOSED SPRING LIFTING MECHANISM FOR MAX. 30 LBS. OPENING FORCE
 - 6- AREA OF FRAME IN CONTACT WITH CONCRETE TO BE PAINTED WITH BITUMINOUS COATING
 - 7- FRAME SPLIT IN 2 SECTIONS FOR SHIPPING & BOLTED TOGETHER IN THE FIELD BY OTHERS

EEH - EMERGENCY EGRESS HATCH

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M		U.S.A.: info@acudor.com / 800.722.0501	
BREAK ALL SHARP CORNERS & EDGES TO 0.01		CANADA: info@acudor.ca / 844.228.2671	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		INTERNATIONAL: info@acudorint.com	
INCHES = ± 1/16		(905) 428.2240	
1/16 = ± 1/32		SCALE: 1=12	SHEET: 1 of 1
1/32 = ± 1/64		DATE: 5/6/19	REV: 0
DRAWN BY: DAV	CHECKED BY: DAV	DATE: 1000125971	REV: 0