

AL-9500

SPECIALTY DOORS

Anti Ligature Access Door

Application

- Designed for Anti-Ligature Installation
- Designed to provide a fully gasketed fit in all types of walls and ceilings
- This door is commonly used in prisons, correctional facilities, psychiatric Hospitals, etc.

Product Features

- Fully gasketed access door
- Formed door panel with reinforced edges and a concealed hinge, along with closed cell gasket between the door and frame
- Fully welded frame flange, radiused corners

AL-9500 Access Door Specifications:

Door / Door Frame: Steel: 14 gauge door, 14 gauge mounting frame, flange to be 1" wide. Also available: Stainless Steel.

Hinge: Concealed

Gasket: Pemko S88 adhesive-backed bulb silicone gasket

Standard Latch: Tamper-proof spanner head cam latch

Optional Latches/Locks: Torx head, Cylinder Lock, Mortise Lock, Torx head with security pin

Finish: 5 stage iron phosphate with prime coat of White alkyd baked-on enamel. Also available: Stainless steel: #4 satin polish.



AL-9500 STANDARD SIZES

(other sizes available upon request)

Nominal Door Size W&H		Weight per Door	
Inches	mm	lbs.	kg.
12 X 12	305 X 305	9.0	4.1
16 X 16	406 X 406	10.0	4.5
18 X 18	457 X 457	13.0	5.9
24 X 24	609 X 609	20.0	9.1
24 X 36	609 X 914	31.0	14.1

Wall or ceiling opening is nominal door size + 3/8" (9 mm)
For detailed specifications see submittal sheet

